




PHOTOMETRIC INFORMATION


39° REFLECTOR - CLEAR LENS - 3500K - 90 CRI
AOM-02-39-COB-3W/90/35K
Delivered Lumens: 225.5 lm
System Wattage: 3.66 W
Luminaire Efficacy: 61.6 lm/W



Illuminance at a Distance			Beam Angle 32.6°
	Illuminance at Center	Beam Diameter	
3.3 Ft	502.00 Lux	2.0 Ft	
6.6 Ft	125.50 Lux	3.9 Ft	
9.8 Ft	55.78 Lux	5.9 Ft	
13.1 Ft	31.38 Lux	7.5 Ft	
16.4 Ft	20.08 Lux	9.5 Ft	
19.7 Ft	13.94 Lux	11.5 Ft	

60° REFLECTOR - CLEAR LENS - 3500K - 90 CRI
AOM-02-60-COB-3W/90/35K
Delivered Lumens: 204.3 lm
System Wattage: 3.64 W
Luminaire Efficacy: 56.0 lm/W



Illuminance at a Distance			Beam Angle 57.3°
	Illuminance at Center	Beam Diameter	
3.3 Ft	219.00 Lux	3.6 Ft	
6.6 Ft	54.75 Lux	7.2 Ft	
9.8 Ft	24.33 Lux	10.8 Ft	
13.1 Ft	13.69 Lux	14.4 Ft	
16.4 Ft	8.76 Lux	18.0 Ft	
19.7 Ft	6.08 Lux	21.7 Ft	

COLOR TEMPERATURE MULTIPLIER

	2700K	3000K	3500K	4000K
Multiplier for Lumen	0.90	0.95	1.0	1.04

Photometric performance is measured at an accredited independant laboratory in accordance with IESNA LM-79. Information herein are subject to change without notice.