



PHOTOMETRIC INFORMATION

26° REFLECTOR - CLEAR LENS - 3500K - 90 CRI
SAP-02-26-MD-COB-9W/90/35K
Delivered Lumens: 822.1 lm
System Wattage: 10.27 W
Luminaire Efficacy: 80 lm/W



Illuminance at a Distance			Beam Angle 23.1°
	Illuminance at Center	Beam Diameter	
3.3 Ft	2282.00 Lux	1.3 Ft	
6.6 Ft	570.50 Lux	2.6 Ft	
9.8 Ft	253.56 Lux	3.9 Ft	
13.1 Ft	142.63 Lux	5.3 Ft	
16.4 Ft	91.28 Lux	6.9 Ft	
19.7 Ft	63.39 Lux	8.2 Ft	

60° REFLECTOR - CLEAR LENS - 3500K - 90 CRI
SAP-02-60-MD-COB-9W/90/35K
Delivered Lumens: 824.9 lm
System Wattage: 10.29 W
Luminaire Efficacy: 80.2 lm/W



Illuminance at a Distance			Beam Angle 58.1°
	Illuminance at Center	Beam Diameter	
3.3 Ft	906.00 Lux	3.6 Ft	
6.6 Ft	226.50 Lux	7.2 Ft	
9.8 Ft	100.67 Lux	10.8 Ft	
13.1 Ft	56.63 Lux	14.4 Ft	
16.4 Ft	36.24 Lux	18.3 Ft	
19.7 Ft	25.17 Lux	21.9 Ft	

	COLOR TEMPERATURE MULTIPLIER											
	2700K			3000K			3500K			4000K		
	80+	90+	95+	80+	90+	95+	80+	90+	95+	80+	90+	95+
Multiplier for Lumen	1.06	0.90	0.78	1.11	0.95	0.83	1.14	1.0	0.86	1.17	1.04	0.89

Photometric performance is measured at an accredited independant laboratory in accordance with IESNA LM-79. Information herein are subject to change without notice.