

MAYFAIR Suspension

PRODUCT ORDERING CODE



PRODUCT FEATURES

- Multiple shade options with encapsulated fabrics and materials in high performance resin
- LED engine CRI 90+ available in 2700K | 3000K | 3500K
- White acrylic diffuser at bottom of shade
- Perforated grid on top of shade
- LED available with multiple dimming options
- 5 year product warranty on LED products
- Rated for damp location



Project	
Type	
Quantity	
Note	

PRODUCT CODE		LIGHT SOURCE	OAH
MYSMD	Mayfair Suspension H: 8" W (A): 23.5" W (B): 23.5"	LED28W27K90 28W LED 2700K CRI 90+ 3148 nominal lumens LED28W30K90 28W LED 3000K CRI 90+ 3148 nominal lumens LED28W35K90 28W LED 3500K CRI 90+ 3590 nominal lumens	XX Provide OAH distance from ceiling to the bottom of the luminaire in inches.
MYSLG	Mayfair Suspension H: 10" W (A): 30" W (B): 30"	LED89W27K90 89W LED 2700K CRI 90+ 9263 nominal lumens LED89W30K90 89W LED 3000K CRI 90+ 9263 nominal lumens LED89W35K90 89W LED 3500K CRI 90+ 10841 nominal lumens	
		MB3 3 X 60W 120V Type A-19 incandescent E26 medium base or LED screw-in equivalent (bulbs not included) MYSMD MB6 6 X 100W 120V Type A-19 incandescent E26 medium base or LED screw-in equivalent (bulbs not included) MYSLG	

SHADE	DIMMING	VOLTAGE	FINISH
AC White satin finish acrylic	D010 0-10V 1% dimming LED driver (4 wire)	120V/277V 120V-277V Universal voltage electronic LED driver	01 White paint
KN Imago progeny blonde encapsulated fabric	PHS Forward/Reverse Phase 1% LED dimming driver (2 wire) <i>(only available in 120V)</i>	120V Electronic LED driver (PHS Phase dimming)	02 Black paint
KW Lintel white encapsulated linen	NODIM No dimming option required		08 Dark mat bronze paint
SW Sand dollar white encapsulated linen			21 Polished gold plated
			22 Brushed gold plated
			24 Brushed nickel plated
			31 Polished nickel plated

CUSTOM MODIFICATIONS


- Sloped ceiling adapter and longer stem
- Customizable finishes, sizes and LED specifications
- Emergency battery pack available
- Dali control protocol or Lutron EcoSystem/3-wire dimming LED driver
- Remote driver options available

MAYFAIR Suspension

PRODUCT SPECIFICATION



TECHNICAL DRAWING(S)



DIMENSIONS & WEIGHT

MYSMD H: 8" W (A): 23.5" W (B): 23.5" Net Wt. 38 lbs.

MYSLG* H: 10" W (A): 30" W (B): 30" Net Wt. 57 lbs.

* MYSLG shade option must be mounted or supported independently on an junction box

OTHER SPECIFICATIONS

- Standard stem 5/8" Ø X 48" (not field cuttable, must specify required OAH)
- Standard maximum overall height (MYSMD = 56") - (MYSLG = 58")
- Canopy size 5" Ø
- UL Certified and suitable for damp location

INSTALLATION REQUIREMENTS

- MYSLG shade option must be mounted or supported independently of an electrical junction box
- Mounts to a standard 4" octagonal electrical junction box or plaster ring
- Driver concealed within shade

LIGHT SOURCE SPECIFICATIONS

- Electronic constant current LED power supply
- Consistent binning that falls within 3 MacAdam ellipse
- LED Life, L70 > 84 700 hrs at 70% lumen maintenance
- Integral Class II driver concealed within shade
- Thermally managed within manufacturer specifications to maximize LED life
- Field replacement for LED module and driver is simple & requires minimal effort
- LED module made in Canada
- No ultraviolet or infrared, alleviating potential damage to art, fabric & materials
- Electrical components are mercury free and are RoHS compliant

COMPATIBLE DIMMER LIST

Compatibility dimmer list available on our website:
www.hemeralighting.com/dimming