

SVELTE Wall Sconce

PRODUCT ORDERING CODE



PRODUCT FEATURES

- Plated or painted aluminum structure providing direct lighting
- LED engine CRI 90+ available in 2700K | 3000K | 3500K
- LED engine is covered with a secured white frosted acrylic diffuser for easy cleaning and preservation of LED integrity
- Can be installed horizontally or vertically
- LED available with multiple dimming options
- ADA compliant
- 5 year product warranty on LED products
- Rated for damp location



Project

Type

Quantity

Note

PRODUCT CODE		LIGHT SOURCE	
SEWMDRP	Medium Svelte Wall Sconce - 20" H X 3" W X 2.625" P Rectangular back plate	LED9W27K90	9W LED 2700K CRI 90+ 1280 nominal lumens (SEWMD)
SEWMDSP	Medium Svelte Wall Sconce - 20" H X 5" W X 2.625" P Square back plate	LED9W30K90	9W LED 3000K CRI 90+ 1315 nominal lumens (SEWMD)
		LED9W35K90	9W LED 3500K CRI 90+ 1325 nominal lumens (SEWMD)
SEWLGRP	Large Svelte Wall Sconce - 36" H X 3" W X 2.625" P Rectangular back plate	LED13W27K90	13W LED 2700K CRI 90+ 2085 nominal lumens (SEWLG)
SEWLGSP	Large Svelte Wall Sconce - 36" H X 5" W X 2.625" P Square back plate	LED13W30K90	13W LED 3000K CRI 90+ 2145 nominal lumens (SEWLG)
		LED13W35K90	13W LED 3500K CRI 90+ 2160 nominal lumens (SEWLG)


DIMMING		VOLTAGE		FINISH	
D010	0-10V 1% dimming LED driver (4 wires)	120V/277V	120V-277V Universal voltage electronic LED driver	01	White paint
PHS	Forward/Reverse Phase 1% LED dimming driver (2 wire) <i>(only available in 120V)</i>	120V	Electronic LED driver (PHS Phase dimming)	02	Black paint
NODIM	No dimming option required <i>details</i>			08	Dark mat bronze paint
				12	Antique gold paint
				21	Polished gold plated
				22	Brushed gold plated
				24	Brushed nickel plated
				31	Polished nickel plated

CUSTOM MODIFICATIONS



- Customizable finishes, sizes and LED specifications
- Emergency battery pack available
- Dali control protocol or Lutron EcoSystem/3-wire dimming LED driver
- Remote driver

SVELTE Wall Sconce

PRODUCT SPECIFICATION



TECHNICAL DRAWING(S)



DIMENSIONS & WEIGHT

SEWMDRP	H: 20" W: 3" P: 2.625" Net Wt. 3 lbs.
SEWMDSP	H: 20" W: 5" P: 2.625" Net Wt. 3 lbs.
SEWLGRP	H: 36" W: 3" P: 2.625" Net Wt. 4 lbs.
SEWLGSP	H: 36" W: 5" P: 2.625" Net Wt. 4 lbs.

OTHER SPECIFICATIONS

- Center of electrical junction box to top of fixture vertical mount (SEWMD = 10") - (SEWLG = 18")
- Center of electrical junction box to top of fixture horizontal mount (SEWMDSP = 2.5") - (SEWMDRP = 1.5")
- Center of electrical junction box to top of fixture horizontal mount (SEWLGSP = 2.5") - (SEWLGRP = 1.5")
- Canopy size (SEW_SP = 4.5" H X 4.5" W) - (SEW_RP = 5.5" H X 2.5" W)
- UL Certified and suitable for damp location

INSTALLATION REQUIREMENTS

- SEW_SP back plate option mounts to a 4" octagonal electrical junction box or plaster ring
- RP back plate option mounts to a switch box (minimum switch box dimensions = 2.25" W X 2.5" D)
- Driver to be fitted in junction box

LIGHT SOURCE SPECIFICATIONS

- Electronic constant current LED power supply
- Consistent binning that falls within 3 MacAdam ellipse
- LED Life, L70 > 60 000 hrs at 70% lumen maintenance
- Integral Class II driver
- Thermally managed within manufacturer specifications to maximize LED life
- No ultraviolet or infrared, alleviating potential damage to art, fabric & materials
- Electrical components are mercury free and are RoHS compliant

COMPATIBLE DIMMER LIST

Compatibility dimmer list available on our website:
www.hemeralighting.com/dimming

SVELTE Wall Sconce

PRODUCT SPECIFICATION

PHOTOMETRIC DATA

COB9W30K90 MD

Nominal LED Source Wattage: 9W
System wattage: 11.1W
Color accuracy: CRI 90+
Light Color: 3000° K
Delivered lumens: 1038 lm
Luminaire efficacy: 93.3 lm/w

PHOTOMETRIC DATA

COB13W30K90 LG

Nominal LED Source Wattage: 13W
System wattage: 16.0W
Color accuracy: CRI 90+
Light Color: 3000° K
Delivered lumens: 1828 lm
Luminaire efficacy: 114.1 lm/w

COLOR TEMP. MULTIPLIER

2700K	0.97
3000K	1.00
3500K	1.04
4000K	1.09